

Communication interface for **Modbus RTU**

– for automation

The CIM/CIU 200 is a standard interface for data transmission between a Modbus RTU network and a Grundfos pump or controller. It makes data exchange possible between Grundfos pumping systems and a PLC or SCADA system. CIM/CIU 200 can also use the SattCon COMLI protocol.

Extensive amounts of datapoints are available from each product via the CIM/CIU 200. The interface offers uncomplicated system integration with both new and legacy systems, as the Modbus RTU protocol is widely supported by existing control systems and PLCs.

The interface module can be installed as an internal add-on or as a wall-mounted unit where internal connection is not supported. The wall-mounted unit is equipped with a 24-240 VAC/VDC power supply.

In addition to Modbus RTU, interface modules are also available for GENIbus, BACnet, Profibus, PROFINET IO, Modbus TCP, LON, GSM/GPRS (wireless communication) and Grundfos Remote Management.

CIM 200 add-on module

The CIM 200 is an add-on communication module installed internally in 11-22 kW Grundfos E-pumps, MGE model H, Control MPC, Hydro MPC, MAGNA3 or Dedicated Controls, Hydro Multi-B.

CIU 200 wall-mounted/DIN-rail unit

The CIU 200 with internal power supply is for Grundfos products that do not support the add-on module.

Supported products

- > Dry running E-pumps: CRE/CRNE/CRIE, MTRE, CME, TPE Series 1000/2000, NBE/NKE
- > MAGNA/ UPE Circulators * / MAGNA3
- > CUE Motor drive for pumps
- > Wastewater-AUTOADAPT
- > Multi Pump Controller: Control MPC
- > Boosters: Hydro Multi-E and Hydro MPC and Hydro Multi-B
- > CR Monitor* condition monitoring for CR pumps
- > Dedicated Controls for sewage pumps (separate data sheet)
- > Motor Protector MP 204

* additional add-on GENIbus module required

Advantages at a glance

- > Supports a wide range of Grundfos products
- > Simple configuration of Modbus RTU hardware settings
- > Modular design – prepared for future needs
- > 24-240 VAC/VDC power supply in CIU
- > Modbus diagnostics available
- > Transmission speeds up to 38.4 kbs



Using CIM/CIU with Grundfos products

General CIU 200 data

| | |
|------------------------|--|
| Supply voltage | 24-240 VAC/VDC, -10% / + 15% |
| Frequency | 0 - 60 Hz |
| Power consumption | Max. 11 W |
| Cable size | IEC: 0.2 - 4 mm ² , UL: 24-12 AWG |
| Enclosure class | IP 54, according to IEC 60529 |
| Cable entry | 6 x M16 Ø4 - Ø10 |
| Operating temperatures | -20 °C to +45 °C (-4 °F to +113 °F) |
| Storage temperatures | -20°C to +60°C (-4°F to +140°F) |
| Dimensions (H/W/D) | 182 x 108 x 82 mm |

GENIbus Communication

| | |
|------------------------|-------------------------------|
| Protocol | GENIbus |
| Recommended cable type | Screened, double twisted-pair |
| Maximum cable length | 1200 m/ 4000 ft |

Modbus Communication

| | |
|----------------------|--|
| Protocol | Modbus RTU, COMLI |
| Transceiver | RS-485 |
| Transmission speeds | 1.2, 2.4, 4.8, 9.6, 19.2, 38.4 kbits/s |
| Parity settings | Even or no parity |
| Modbus Slave address | 1 – 247, set via rotary switches |

Modbus RTU network



Data points

| CIM/CIU 200 Modbus | MAGNA / UPE | MAGNA3 | E-Pumps 0.25-7.5 kW | CUE / E-Pumps 11-22 kW | Multi-E | Hydro MPC/ Control MPC | MP 204 | Hydro Multi-B |
|--|-------------|--------|------------------------|---------------------------|---------|---------------------------|--------|---------------|
| s = if sensor installed s* = available with sensor or TPE 2000 ¹ differential or absolute, depends on sensor ² Not standard for Control MPC ³ Not supported for all pump variants G = only for MGE model G H = only for MGE model H | | | | | | | | |
| Control | | | | | | | | |
| Operating Mode | • | • | • | • | • | • | • | • |
| Setpoint | • | • | • | • | • | • | • | • |
| Control Mode | • | • | • | • | H | • | • | • |
| Relay Control | | | • | • | | | | |
| Tank filling control | | | | | | | | • |
| Status | | | | | | | | |
| Operating Mode Status | • | • | • | • | • | • | • | • |
| Control Mode Status | • | • | • | • | • | • | • | • |
| Feedback | • | • | • | • | • | • | • | • |
| Alarm/warning information | • | • | • | • | • | • | • | • |
| Bearing Service information | | | H | • | | | | |
| Tank filling status information | | | | | | | | • |
| Measured Data | | | | | | | | |
| Power/Energy Consumption | • | • | • | • | • | • | • | • |
| Pressure (Head) ¹ | • | • | s* | s* | • | s* | | s |
| Flow | • | • | s* | s* | H+s | s* | | |
| Relative Performance | • | • | • | • | • | • | | • |
| Speed and Frequency | • | • | • | • | | | | |
| Digital Input/Output | • | • | • | • | • | • | • | • |
| Motor Current | | • | • | • | • | | • | |
| DC Link Voltage | • | • | • | • | | | | • |
| Motor Voltage | | | • | • | | | | |
| Remote Flow | | s | G+s | s | H+s | | | |
| Inlet Pressure ¹ | | | G+s | s | H+s | s | | s |
| Remote Pressure ¹ | | s | G+s | s | H+s | s | | |
| Level | | | s | s | H+s | s | | s |
| Motor Temperature | | | G | • | | | | s |
| Remote Temperature | | s | s | s | H+s | s | | |
| Pump Liquid Temperature | • | • | G+s | s | | | | |
| Bearing Temperatures | | | H+s | s | | | | |
| Auxiliary Sensor Input | | | s | s | H+s | | | |
| Operation Time (Run Time) | • | • | • | • | • | • | • | • |
| Total on time | • | • | • | • | • | • | • | • |
| Number Of Starts | • | • | • | • | • | • | • | • |
| Ambient Temperature | | | H+s | | H+s | s | | |
| Inlet and Outlet Temperatures | | | | | | s | | |
| Heat energy meter | • | | H | | | | | |
| Outlet Pressure ¹ | | | H+s | | H+s | s* | | s |
| Feed Tank Level | | | H+s | | H+s | s | | s |
| Phase Voltages | | | | | | | | • |
| Line Voltages/Currents/Frequency | | | | | | | | • |
| Start/Run Capacitor | | | | | | | | • |
| Voltage Angles + Cos phi | | | | | | | | • |
| Insulation resistance | | | | | | | | • |
| Starts/h and auto restarts/24h | | | | | | | | • |
| Subpump Data (for each sub pump in the system) | | | | | | | | |
| Alarm/Status information | | | | | • | • | | • |
| Operation Time (Run Time) | | | | | • | • | | • |
| Speed | | | | | H | • | | • |
| Line current/ power consumption | | | | | H | • | | • |
| Motor temperature | | | | | H | • | | • |
| Number of starts | | | | | H | • | | • |
| Control pump: force to stop/ auto | | | | | | • | | • |

Note: E-Pumps = CRE/CRNE/CRIE, MTRE, CME, TPE Series 1000/2000, NBE/NKE.
 Note: For WW-AutoAdapt pumps and Dedicated Controls view to related datasheets
 Note: TPED twin pumps in range 3,0 -22 kW needs always 2 CIU modules
 Note: For DDA dosing pumps please view to related datasheets